EHI-B WEIGHING INDICATOR



Features

Application: Widely used to work with shipping scales, livestock scales, physician scales,

platform scales, floor scales and much more.

• **Resolution**: Up to 1/100,000 display resolution

Construction: Compact and simple design for both wall and desk using

Stainless steel enclosure equipped with desk/column mount bracket provides

years of service in normal application

• Display: 5½ digits 17mm(0.625")7-segment LCD with optional backlight for comfortable reading

• Units of measuring: kg, lb, lb:oz

Power: 6V 500mA AC adapter (included) or 4xAAA batteries (not included)

• Communication: Optional RS232 interface allow to transmit data to PC

• Function: Full range tare, auto zero tracking, programmable power-off, low power and

overload indication, weighing, simple counting

Specifications

Item	Parameters
Display	LCD display with optional backlight
Function Keys	UNIT, TARE, ON/OFF/ZERO
Power	6VDC 500mA adapter (included) or 4xAAA batteries (not included)
Loadcell capability	4@350 ohm
Excitation voltage	5V DC
Communication	Full duplex RS232 interface
Dimensions	162mm(L)x80mm(W)x29mm (H) / 6.4" (L) x33.2" (W) x81.2" (H)
Packing size	57x47x54cm/20pcs/ctn G.W.:28kg N.W.:26kg
Operation Temp	0°C to 40°C (32°F to 104°F)
Options	RS232 cable, load cell cable

