

CSG LPB WEIGH-BEAMS WITH INDICATOR



The LPB portable 'weigh-beams with indicator' combination is easy to set up using quick connectors. It is a flexible heavy duty industrial weighing solution, ideal for when high capacity weighing is required, but there is insufficient space for a permanently fixed scale. This system is equally at home with awkward or long loads as they are with pallet loads etc. The supplied armoured cables allow the beams to be placed up to 6 metres apart. It can be used as a platform scale if a large metal plate is put on the beams and the reading re-zeroed.

Each beam has a carrying handle at one end and a roller wheel at the other to permit easy movement.

Supplied with the proven LP7510 weighing indicator.

SPECIFICATIONS

Capacity: 3 Tonnes

Division size: 0.5 Kg.

Shipping weight: 50 kg.

Beam length: 1200 mm.

Beam Height: 70 mm.

Beam width: 100 mm.

Indicator: CSG LP7610 Stainless steel.

Power: Internal rechargeable battery, charger supplied

CSG LP7510 WEIGHING INDICATOR



CSG LP7510 SPECIFICATIONS

High quality, low cost weighing indicator in a durable stainless steel case.

Dimensions: 7.87" long x 2.95" wide x 7.17" high.

Large, easy to read 6 digit LED display

Charges in 6 to 8 hours.

Zero, gross, net, counting & animal weighing modes.

Tare function

Weighs in Pounds or Kilograms

Capable of powering up to 6 x 350 ohm load cells

Display resolution 30,000

Internal count resolution 2,000,000

Supply voltage 100-250v

6v 4ah. internal rechargeable battery

Operating temperature -10 to 40 C.

Storage temperature - 40 to 70 C.

Suitable for Wall, Table or Column mounting.