











Waterproof - Scale suitable for use outside

TN Crane Scales

General Specifications

Display

Capacities

Keyboard

Housing

Max. Divisions

ADC

ADC update Operate Temp

Power

30mm digits LCD display with LED backlight (TN-LCD)

600ka~12t

5 keys(Mechanical switch)

Die-casting aluminum

3x3,000d

Sigma delta

≤1/10 second

-10°C~+40°C

AC adapter(12V/2500mA),

Rechargeable Li battery 7.4V 5200mA



Application: Tare, Hold, Accumulation, Weighing Units Conversion

Waterproof

Triple range (3 x 3000 divisions)

Internal Li-lon rechargeable battery 60hrs continuous use (without backlight)

Remote Controller

Bluetooth

APP for mobile Phone

Records Management







TN Crane Scales

Model Name	Capacity	Readability	Division	Approx. weight
TN-600kg	150kg/300kg/600kg	0.05kg/0.1kg/0.2kg	3x3,000d	11kg
TN-3000kg	600kg/1500kg/3000kg	0.2kg/0.5kg/1kg	3x3,000d	11kg
TN-12000kg	3000kg/6000kg/12000kg	1kg/2kg/5kg	3x3,000d	25kg










APP for android

Dimensions(mm)







DIM (mm) CAP	600kg	3T	12T
A	201	201	201
В	160	160	160
С	128. 5	128. 5	128. 5
D	80	80	95
Е	60	60	80
F	270	275	330
G	219	219. 5	247.5
Н	Ф 19	ф 22	ф 31. 8
J	ф 50. 8	Ф 58	Ф 82. 5
L	ф 23	Ф 26. 5	Ф 36
M	Ф 23	ф 26. 5	Ф 36
N	415	456	557
P	477	532	660
Q	42. 9	50.8	63. 5